

CEYTREYLER TECHNICAL SPECIFICATIONS

	UNIT	84 CBM SCRAP TIPPER	
MATERIALS	Manufacturer	Ceytech Makine San. Ve Tic. A.S	
	Volume	84 m ³	10.120
	Floor	5mm	HB450
	Side walls (2 pcs.)	4mm/ 3mm	HB450
	Front wall	4mm	HB450
	Rear door	4mm	HB450
	Chassis	Formed by high strength S700 steel welded in submerged arc welding robots.	
	FEATURES	King pin	2 " Sized flange type screwed from underneath/JOST
Balance leg		Dual speed mechanical jack with 24 ton dynamic 50 ton static lifting capacity, LT ALU leg	
Undercarriage		3 axles with 9 ton capacity SAF Disc 430 CD Type Axle	
Suspension		SAF 6 air suspension/ 1 front axel lifting	
Brake System		Dual circuit pneumatic WABCO EBS brakes according to EEC standards.Load balancing distribution valve, Automatic brake adjustment arms with emergency brake system. Raise to adjust level– Lower valve. All valves are."WABCO" brand. Brake ratchets are automatic./With a dual-circuit pneumatic compliance with EU regulations, a WABCO EBS 4S/2M braking system	
Wheels		6	385x65 R 22,5 Bridgestone/Pirelli/Lassa Tubeless tires. 6 x Steel Rims ET120/11.75X22.5
Electric System		The electrical system includes park and warning lights on both sides along with a park,signal,stop and plate lights at the rear/7 and 15 ASPOCK electrical systems and lighting projectors in accordance with EU regulations	Aspöck
		2 x LED headlights rear/Reverse light	
	2 x LED spotlights on the landing gear		
Hydraulic system	Telescopic cylinder that is a single action C type HYVA Branded/Cold draft hydraulic lift, direction control, and level valve HYVA		
ACCESSORIES	"E37" documented reflectors		
	1x PVC Tool Box		
	Red Strip reflector		
	Mudguards		
OPTIONS	Hydraulic Rear Door		
	No Tarpaulin		
	KTL Chassis		
SURFACE	Paint		
	Colour	Gray	

